

| PROPERTY | UNIT | GUARANTEE | LIMIT | TEST METHOD |
|----------------------------------|----------|-------------|-------|---|
| Appearance | | Homogeneous | | Visual |
| Color | | 2,0 | Max | ASTM D 1500 |
| Density (at 15 °C) | kg/l | Report | | TS 1013 EN ISO 3675 TS EN ISO 12185 ASTM D 4052 |
| Carbon Residue | % wt | 0,1 | Max | TS 6148 EN ISO 10370 ASTM D 4530 |
| Flash Point | °C | 200 | Min | TS EN ISO 2592 ASTM D 92 |
| Pour Point | °C | -3 | Max | TS 1233 EN ISO 3016 ASTM D 5950 ASTM D 97 |
| Viscosity Kinematic (at 40 °C) | cSt | Report | | TS 1451 EN ISO 3104 ASTM D 445 |
| Viscosity Kinematic (at 100 °C) | cSt | 5,0-5,7 | | TS 1451 EN ISO 3104 ASTM D 445 |
| Viscosity Index | | 99 | Min | TS ISO 2909 ASTM D 2270 |
| Sulfur | % wt | 0,03-5,0 | | TS EN ISO 8754 IP 336 |
| Saturated Hydrocarbon Content | % wt | 50-89 | | TS 6596 |
| Hydrocarbon Content, Aromatic | % wt | 15 | Max | TS 6519 |
| NOACK | % | 25 | Max | TS 13489 ASTM D 5800 |
| Acid Number | mgKOH/g | 0,1 | Max | TS 9178 ISO 6618 ASTM D 664 |
| Basic Number | mg KOH/g | 1,2 | Max | TS 5655 ISO 3771 ASTM D 2896 |
| Water | mg/kg | 150 | Max | TS 6147 EN ISO 12937 ASTM D 6304 |

This product is produced only in İzmir Refinery.